

*Befüringer
KCTC*

REC'D MAY 03 2005

EG/ISO Sicherheitsdatenblatt Safety Data Sheet

1/4
Überarbeitet am: 08.12.1997

1. Identification of the substance/preparation

Identification of the substance or preparation:

Name of product: AUTOSOL CHROME and METAL-POLISH

Manufacturer/distributor identification

Dursol-Fabrik

Martinstr. 22

42655 Solingen

Telefon: 0212 2718-0

Postfach 190210

42702 Solingen

Telefax: 0212 208795

Emergency phone: 0212 2718-0

For further emergency information call any „Informations- und Behandlungszentren für Vergiftungen (Vergiftungszentralen)“ in Germany.

Refer to Mittelkarten-Nr.: 5729 Art. No. 1000, 1100

2. Composition / information on ingredients

Chemical characterization (substance):


Emulsion on base of water-/hydrocarbons with:

Aliphatic/aromatic hydrocarbons,
care components, polishing agents,
fragrances.

3. Possible hazards.

unknown

(see point 8)



Autosol Chrome and Metal-Polish

4. First aid measures

Skin contact: In case of contact with skin wash off immediately with soap and water.

Eye contact: In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion: Do not induce vomiting. Seek medical advice immediately.

5. Fire-fighting measures

Suitable extinguishing material: carbon dioxide, dry powder, foam, water.

Extinguishing material that must not be used for safety reasons: none

Special exposure hazards extinguishing from the substance or preparation itself, combustible products or resulting gases: unknown

Special protective equipment for firefighters: none

6. Accidental release measures

Personal precautions: Use personal protective clothing.

Methods for cleaning up/taking up: Take up mechanically.
Do not discharge into the drain.

7. Handling and storage

Advice on safe handling: Provide good room ventilation.

Advice on protection against fire and explosion: No special measures necessary.



Sicherheitsdatenblatt

Seite :
Überarbeitet am:

3/4
08.12.1997

Autosol Chrome and Metal-Polish

8. Exposure controls/personal protection

Ingredients with occupational exposure limits to be monitored:

Low aromatic hydrocarbons below 25 %

CAS-Nr.: 64742-82-1 (benzene < 0,1%)

Limit for hydrocarbons at place of work: 100 ml/m³

100 % ammonia less than 1 %

CAS-Nr.: 7664-41-7

MAK: 50 ppm or 35 mg/m³

Personal protection equipment: Gloves are recommended for intensive use over longer periods. Avoid contacts with eyes.

Hygiene measures: Keep away from food and drink.

9. Physical and chemical properties

Form: paste

Colour white-grey

Odour: caramel-like

Changes in physical state:

melting point below 0 °C

Boiling range from approx. 100 °C

Flash point: none under 100 °C

Density: (at 20 °C) 1,1 g/ml

Solubility in water: limited mixable

pH-Wert (at 10 g/l water): approx. 9,5

Viscosity: pasty

10. Stability and reactivity

Hazardous decomposition products: unknown

11. Toxicological information

The product is slightly resorbed by mucous membrans.



Sicherheitsdatenblatt

Seite 08.12.1997
Überarbeitet am: 4/4

Autosol Chrome and Metal-Polish

12. Ecological information

German national legislation:

Water hazard class (self-assessment): WGK 2 (endangerous for water)

13. Disposal considerations

European legislation:

EWC-Code 07 06 99 n.o.s.

14. Transport information

GGVSee/IMDG-Code: not classified

UN-No.: not classified

GGVE/GGVS and RID/ADR: not classified

ICAO/IATA-DGR: not classified

ADNR:

15. Regulatory information

Labelling: not classified

Classification according to VbF/remarks: none

Water hazard class (self-assessment): WGK 2 (endangerous for water)

Autosol Chrome and Metal-Polish is a composition.

All ingredients are listed in TSCA.

16. Other information

none.

Die Angaben in diesem Sicherheitsdatenblatt stützen sich auf den heutigen Stand der Kenntnisse und Erfahrungen und soll dazu dienen, die Produkte im Hinblick auf etwaige Sicherheitserfordernisse zu beschreiben. Diese Angaben stellen keine rechtlich verbindliche Zusicherung bestimmter Eigenschaften dar.

DURSOOL-FABRIK - Martinsstraße 22 - D-43686 Galingen - Tel. 0212/27496 - Fax 0212/208796