## U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,

Shipbuilding,	nd Si	hipbreskin	ng (29 CFR 1915, 19	16, 1917)		
, , , , , , , , , , , , , , , , , , ,		SEC1	ION I			
MANUFACTURER'S NAME Hercules Chemical Compar	-		•	EMERGENCY TELEPHON 212-869-4330	YE NO.	
ADDRESS (Number, Street, City, State, and ZIP Co. 29 West 38th Street, New Yo CHEMICAL NAME AND SYNONYMS	<i>dei</i> ork,	NY10	0018 TRADE N	AME AND SYNONYMS		
CHEMICAL FAMILY CONIC SEALANT &	à s	top le	FORMULA		e -	HIL
SECTION	11 -	HAZAF	RDOUS INGREDI	ENTS		
PAINTS, PRESERVATIVES, & SOLVENTS	×	TLV (Units)	ALLOYS AND I	METALLIC COATINGS	×	TLV (Units)
PIGMENTS			BASE METAL			
CATALYST			ALLOYS			
VEHICLE			METALLIC COATING	35		
SOLVENTS			FILLER METAL PLUS COATING OR (	CORE FLUX		
ADDITIVES -			OTHERS			
OTHERS						
HAZARDOUS MIXTURES	OF C	THER LIC	DUIDS, SOLIDS, OR G	ASES	*	TLV (Units)
Not Appli	ical	ole				
•						
				•		
SEC.	TIO	N 111 - P	PHYSICAL DATA			
BOILING POINT (°F.)	T		SPECIFIC GRAVITY	(H <sub>2</sub> O=1)		
VAPOR PRESSURE (mm Hg.)	1		PERCENT, VOLATIL	Ε		
VAPOR DENSITY (AIR-1)			EVAPORATION RAT			

SECTION III - PHYSICAL DATA				
BOILING POINT (°F.)	SPECIFIC GRAVITY (H20=1)			
VAPOR PRESSURE (mm Hg.)	PERCENT, VOLATILE BY VOLUME (%)			
VAPOR DENSITY (AIR=1)	EVAPORATION RATE			
solubility in water miscible in water				
APPEARANCE AND ODOR bluish green color	red liquid			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (Method used	1)	FLAMMABLE LIMITS	Lel	Uel		
EXTINGUISHING MEDIA	Dry Chemical, Foam,	co <sub>2</sub>		<u></u>		
SPECIAL FIRE FIGHTING	PROCEDURES					
	NONE					
UNUSUAL FIRE AND EXP	OSION HAZARDS					
	NOME					

		SECTION	V - HEALTH HAZARD DATA
		SECTION	V - REALIN HAZARD DATA
THRESHOLD LIN	MIT VALUE		
EFFECTS OF OV	EREXPOSURE I	rritant	to the eyes.
	•	•	
EMERGENCY AN	ND FIRST AID PROCE	DURES	
Skin -	- wash with	soap ar	nd water.
Eyes -	- wash withc	opious	quantities of water.
		SECTIO	ON VI - REACTIVITY DATA
STABILITY	UNSTABLE		CONDITIONS TO AVOID

STABILITY	บพรา	UNSTABLE X		CONDITIO	ONDITIONS TO AVOID		
	STA						
INCOMPATABIL	TY (Mater	ials to avoid)	- <u></u>				
HAZARDOUS DE	COMPOSI	TION PRODU	Omay	be for	ned during combus	stion.	
HAZARDOUS		MAY OCCI	Z		CONDITIONS TO AVOID	e transferência Hijê dire	
POLYMERIZATION		WILL NOT	OCCUR	×			

···	SECTION VII - SPILI	L OR LEAK PROCEDURE	ES	
STEPS TO	BE TAKEN IN CASE MATERIAL IS RELEASED OR	R SPILLED.		
Ha	ndle as an oil spill.			
WASTE DIS	SPOSAL METHOD		•	
In	ncinerate			

	SECTION VIII - SPECIAL P	ROTECTION INFORMATION	
RESPIRATORY PRO	TECTION . ipecify type) Not needed	3	
VENTILATION	LOCAL EXHAUST Not needed		
	MECHANICAL (General) Not neede	я ванто	Military.
PROTECTIVE GLOV		Not normally needed	****

SECTION IX - SPECIAL PRECAUTIONS					
PRECAUTIONS TO BE TAKEN I	N HANDLING AND STORING				
	None				
OTHER PRECAUTIONS					
	None				