

ITEM: 1DYE3 - Compact Drill/Driver Kit 18.0 VDC.

ORDER: 0110826346

LP NUMBER: U853385237

MSDS: L4199

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - L4199

Associated Grainger Items
 32W70, 3A566, 4PD97, 4PD99, 6A720, 3XU99, 3XY10, 3XY11, 3WU70, 5PP48, 3WU68
 3XU75, 1XHH6, 1XHH7, 1MZV3, 1MZV4, 3LMZ4, 8AYU0, 8DUL2, 8UXJ4, 8VU06, 8VU08
 3XU99, 9V755, 9VW99, 2VJ51, 3EA78, 3EA79, 3EA81, 3HU72, 3HU75, 3HU77, 6NE25
 1MZV5, 1MZV6, 5AB52, 1CVH9, 2CDCS, 2CDC7, 2VJ53, 2VJ54, 2VJ56, 4LEP9, 4LER9
 4ZAS3, 5XEZ7, 2CDC8, 2PY11, 2PY12, 2PY14, 2PY16, 2PY21, 2PY22, 2PY23, 2PY24
 2PY28, 2KXZ3, 4LEP6, 4ZA86, 4ZA88, 4ZA90, 4ZA92, 4ZA94, 4ZA95, 1ELD7, 1ELD8
 1ELD9, 1ELE1, 1VXW1, 1VXW4, 1VXW6, 1VXW7, 1VXW8, 1VXW9, 1VXW1, 1VXW3, 2VJ22, 2VJ23, 2VJ24
 2VJ27, 2MY66, 2MY77, 2PY12, 2PY15, 2PY17, 2PY18, 2PY19, 2PY25, 4FTH3, 4LEP7
 4LEK1, 4LER2, 4LET1, 4LET3, 4LET4, 4LET5, 4LET6, 4PKV6, 4PKV8, 4PKV5, 5GJW5
 6AWL2, 6ENB8, 1DYE3, 4LEP8, 4PKV7, 6AWC5, 6AWC6, 6AWL3, 2PYX6, 2PYX7
 2PYX8, 2PYX9, 2RFU1, 2XKZ6, 4LER3, 4LER4, 4LET2, 4PKU5, 4PKU6, 4PKU7, 4PKV1
 4PKV2, 4PKV3, 5HKL5, 5HKN2, 6AWL5, 4PK22, 4PKY2, 6ALK3, 12E731, 12E732, 12E733
 12E734, 12E735, 11A182, 11A183, 11A184, 11A185, 11A186, 11A187, 11A188, 11A189
 11A190, 11A191, 11A192, 11A193, 11A194, 11A195, 11A196, 11A197, 14F259, 14F260
 14F261, 14F262, 14F263, 14F264, 14F265, 14G946, 14G947, 16T949, 14P345, 26X067
 26X068, 26X069, 26X070, 26X071, 26X072, 24U047, 24U048, 24U049, 24U050, 24U051
 24U052, 24U059, 24U060, 24U061, 24U062, 24U063, 24U064, 24U071, 24U072, 24U073
 24U074, 24U075, 24U076, 24U085, 24U086, 24U087, 24U088, 24U089, 24U090, 6PED4
 8NT27, 34G844, 34G845, 34G846

MILWAUKEE (R*)

MATERIAL SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200.

THIS STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

MILWAUKEE ELECTRIC TOOL CORPORATION
 13135 WEST LISBON ROAD
 BROOKFIELD, WISCONSIN USA 53005-2550

COMPANY PHONE NUMBER: 1-262-781-3600 OR 1-800-729-3878 (SANDUST)

EMERGENCY CONTACT NUMBER: 1-800-424-9300

FOR INTERNATIONAL: 1-703-527-3887

PRODUCT NAME:

LITHIUM-ION BATTERIES, RECHARGEABLE
 CAT. #48-11-0490: RATED 4-VOLTS, 0.9G ELC, 11 WH (MAXIMUM)
 CAT. #48-11-1815: RATED 18-VOLTS, 2.1G ELC, 27 WH (MAX.)
 CAT. #48-11-1828: RATED 18-VOLTS, 3.9G ELC, 47 WH (MAX.)
 CAT. #48-11-1830: RATED 18-VOLTS, 4.5G ELC, 57 WH (MAX.)
 CAT. #48-11-2401: RATED 12-VOLTS, 1.3G ELC, 16 WH (MAX.)
 CAT. #48-11-2402: RATED 12-VOLTS, 2.5G ELC, 32 WH (MAX.)
 CAT. #48-11-2830: RATED 28-VOLTS, 6.3G ELC, 80 WH (MAX.)

DRAWING NUMBER: 58-97-0500 REV. 4A

ISSUE DATE: JANUARY 1, 2009

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

APPEARANCE/ODOR: SOLID ARTICLE, ODORLESS

WARNING: NO EXPOSURE DURING ROUTINE HANDLING OF PRODUCT.

HYDROFLUORIC ACID EXPOSURE DURING FIRE FIGHTING:

THIS INFORMATION IS GIVEN FOR THE USE OF PROFESSIONAL FIRE FIGHTERS
 RESPONDING TO A WAREHOUSE FIRE WHERE FIRE FROM OTHER MATERIALS MAY
 INCINERATE BATTERIES. THIS SECTION IS PROVIDED SOLELY IN CASE OF EXPOSURE,
 DURING FIRE FIGHTING, TO THE COMBUSTION BY-PRODUCTS.

FLAMMABLE:
 ORGANIC COMPONENTS WILL BURN IF CELL IS INCINERATED. COMBUSTION OF CELL
 CONTENTS MAY CAUSE EVOLUTION OF HYDROGEN FLUORIDE.

POTENTIAL HEALTH EFFECTS:
 FLUORIDE INTERFERES WITH NERVE IMPULSE CONDUCTION CAUSING SEVERE PAIN OR
 ABSENCE OF SENSATIONS

LIKELY ROUTES OF EXPOSURE:

EYE CONTACT, SKIN CONTACT, SKIN ABSORPTION, INHALATION. HYDROFLUORIC ACID IS
 EXTREMELY CORROSIVE. CONTACT WITH HYDROGEN FLUORIDE FUMES IS TO BE AVOIDED.
 PERMISSIBLE EXPOSURE LIMIT IS 3 PPM. IN CASE OF CONTACT WITH HYDROGEN
 FLUORIDE FUMES, IMMEDIATELY LEAVE THE AREA AND SEEK FIRST AID AND EMERGENCY
 MEDICAL ATTENTION. SYMPTOMS MAY HAVE DELAYED ONSET. FLUORIDE IONS PENETRATE
 SKIN READILY CAUSING DESTRUCTION OF DEEP TISSUE LAYERS EVEN BONE. FLUORIDE
 INTERFERES WITH NERVE IMPULSE CONDUCTION CAUSING SEVERE PAIN OR ABSENCE OF
 SENSATIONS. IMMEDIATELY FLUSH EYES OR SKIN WITH WATER FOR AT LEAST 20
 MINUTES TO NEUTRALIZE THE ACIDITY AND REMOVE SOME PERSONAL POSSESSIONS. BEFORE
 DESTROY ALL CONTAMINATED CLOTHING AND PERMEABLE PERSONAL POSSESSIONS. BEFORE
 RE-USE, IMPERMEABLE POSSESSIONS SHOULD BE SOAKED IN BENZALKONIUM CHLORIDE
 AFTER WASHING. FOLLOWING FLUSHING OF THE AFFECTED AREAS, AN ICED AQUEOUS
 SOLUTION OF BENZALKONIUM CHLORIDE OR 2.5% CALCIUM GLUCONATE GEL SHOULD BE
 APPLIED TO REACT WITH THE FLUORIDE ION. COMPRESSED AND WRAPS MAY BE USED FOR
 AREAS WHERE IMMERSION IS NOT PRACTICAL. MEDICATED DRESSING SHOULD BE CHANGED
 EVERY 2 MINUTES. EXPOSURE TO HYDROFLUORIC ACID FUMES SUFFICIENT TO CAUSE
 PAIN REQUIRES IMMEDIATE HOSPITALIZATION FOR MONITORING FOR PULMONARY EDEMA.

SECTION 3: COMPOSITION / INFORMATION OF INGREDIENTS

INGREDIENT	% BY WEIGHT	CAS #
ALUMINUM FOIL	0.1 - 10	7429-90-5
BIPHENYL (BP)	0.1 - 0.3	92-52-4
COPPER FOIL	0.1 - 10	7440-50-8

LINEAR & CYCLIC CARBONATE SOLVENTS

0 - 17 N/A

GRAPHITE POWDER/CARBON

10 - 30 7440-44-0

METAL OXIDE OR OTHER ELECTROLYTE (PROPRIETARY)
CONFIDENTIAL

10 - 50

LITHIUM HEXAFLUOROPHOSPHATE (LiPF6)

0 - 5 21324-40-

POLYVINYLIDENE FLUORIDE (PVDF)

0.1 - 5 24937-79-9

STYRENE BUTADIENE RUBBER (SBR)

<5 N/A

ALUMINUM, STEEL, NICKEL AND OTHER INERT MATERIALS

REMAINDER N/A

SECTION 4: FIRST AID MEASURES

NO EXPOSURE DURING ROUTINE HANDLING OF PRODUCT. RISK OF EXPOSURE OCCURS ONLY
 IF THE BATTERY IS MECHANICALLY OR ELECTRICALLY ABUSED.

EYE CONTACT: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT:
 IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. WASH WITH SOAP AND
 WATER

INHALATION: N/A

INGESTION:

INGESTION IS NOT LIKELY, GIVEN THE PHYSICAL SIZE AND STATE OF THE CELL.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL POWDER OR APPROPRIATE FOAM. USE
 AGENT APPROPRIATE FOR SURROUNDING MATERIALS.

UNSUITABLE EXTINGUISHING MEDIA: NONE.

PRODUCTS OF COMBUSTION:

ORGANIC COMPONENTS WILL BURN IF INCINERATED. COMBUSTION OF CELL CONTENTS MAY
 CAUSE EVOLUTION OF HYDROGEN FLUORIDE. IN CASE OF FIRE IN AN ADJACENT AREA,
 USE WATER, CO₂ OR DRY CHEMICAL EXTINGUISHERS IF CELLS ARE PACKED IN THEIR
 ORIGINAL CONTAINERS SINCE THE FUEL OF THE FIRE IS BASICALLY PAPER PRODUCTS.

PROTECTION OF FIREFIGHTERS:

HYDROFLUORIC ACID EXPOSURE DURING FIRE FIGHTING:

THIS INFORMATION IS GIVEN FOR THE USE OF PROFESSIONAL FIRE FIGHTERS
 RESPONDING TO A WAREHOUSE FIRE WHERE FIRE FROM OTHER MATERIALS MAY
 INCINERATE BATTERIES. THIS SECTION IS PROVIDED SOLELY IN CASE OF EXPOSURE,
 DURING FIRE FIGHTING, TO THE COMBUSTION BY-PRODUCTS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

USE STANDARD INDUSTRIAL CLOTHING IN NORMAL USE. IF HANDLING LARGE CONTAINERS
 OF CELLS WEAR STEEL-TOED FOOTWEAR.

ENVIRONMENTAL PRECAUTIONS: NO SPECIAL PRECAUTIONS NECESSARY.

METHODS FOR CONTAINMENT:

TRANSPORT CONTAINER OUTDOORS. HOLD BURNED CELLS AND FIRE CLEANUP SOLIDS FOR
 DISPOSAL AS POTENTIAL HAZARDOUS WASTE. UNBURNED CELLS ARE NOT HAZARDOUS
 WASTE. A FIRE WITH OVER 100 KG OF CELLS BURNT WILL LIKELY REQUIRE REPORTING
 TO ENVIRONMENTAL OFFICIALS. ALWAYS CONSULT AND OBEY ALL INTERNATIONAL,
 FEDERAL AND LOCAL ENVIRONMENTAL LAWS.

METHODS FOR CLEAN-UP:

OTHER INFORMATION:

SECTION 7: HANDLING AND STORAGE

HANDLING:

USE ONLY APPROVED CHARGING EQUIPMENT. DO NOT DISASSEMBLE BATTERY OR BATTERY
 PACK. DO NOT PUNCTURE, CRUSH OR DISPOSE OF IN FIRE.

STORAGE:

STORE IN A COOL, DRY PLACE AWAY FROM SPARKS AND FLAME. KEEP BELOW 125 DEG.
 C. KEEP ABOVE -60 DEG. C. CHARGE BETWEEN 0 DEG. C AND 45 DEG. C.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

ENGINEERING CONTROLS: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

EYE/FACE PROTECTION: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

SKIN PROTECTION: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

RESPIRATORY PROTECTION: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

GENERAL HYGIENE CONSIDERATIONS: NOT NECESSARY UNDER CONDITIONS OF NORMAL USE

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: N/A

ODOR: NONE

ODOR THRESHOLD: NONE

REC'D OCT 18 2012

KCTC
DTC

PHYSICAL STATE: SOLID

pH: N/A

FREEZING POINT: N/A

BOILING POINT: N/A

FLASH POINT: N/A

EVAPORATION RATE: N/A

FLAMMABILITY (SOLID, GAS): ORGANIC COMPONENTS WILL BURN IF CELL IS INCINERATED.

UPPER FLAMMABILITY LIMIT: N/A
LOWER FLAMMABILITY LIMIT: N/A

VAPOR PRESSURE: N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: N/A

SOLUBILITY (WATER): N/A

PARTITION COEFFICIENT (n-OCTANOL/WATER): N/A

AUTO-IGNITION TEMPERATURE: N/A

PERCENT VOLATILE, WT. %: N/A

VOLATILE ORGANIC COMPOUND (VOC) CONTENT, WT. %: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID:
DO NOT CRUSH, PUNCTURE, INCINERATE, IMMERSE IN WATER OR HEAT OVER 212 DEG. F (100 DEG. C). STEEL CASING SLOWLY DISSOLVES IN STRONG MINERAL ACIDS.

INCOMPATIBLE MATERIALS: WATER, HEAT AND STRONG ACIDS

HAZARDOUS DECOMPOSITION:
HYDROGEN FLUORIDE, PHOSPHORUS OXIDES, CARBON MONOXIDE, CARBON DIOXIDE,
LITHIUM HYDROXIDE, MANGANESE OXIDES, ALUMINUM OXIDE, POSSIBLE
FLUORO-COMPOUNDS, CARBON SOOT

POSSIBILITY OF HAZARDOUS REACTIONS:
HAZARDOUS POLYMERIZATION WILL NOT OCCUR. SPONTANEOUS DECOMPOSITION WILL NOT
OCCUR AT NORMAL TEMPERATURE.

SECTION 11: TOXICOLOGY INFORMATION

ACUTE EFFECTS:

ORAL LD50: NONE IN ROUTINE HANDLING OF PRODUCT.
DERMAL LD50: NONE IN ROUTINE HANDLING OF PRODUCT.
INHALATION: NONE IN ROUTINE HANDLING OF PRODUCT.
EYE IRRITATION: NONE IN ROUTINE HANDLING OF PRODUCT.
SKIN IRRITATION: NONE IN ROUTINE HANDLING OF PRODUCT.
SENSITIZATION: NONE IN ROUTINE HANDLING OF PRODUCT.

CHRONIC EFFECT:
CARCINOGENICITY: NONE IN ROUTINE HANDLING OF PRODUCT.
MUTAGENICITY: NONE IN ROUTINE HANDLING OF PRODUCT.
REPRODUCTIVE EFFECTS: NONE IN ROUTINE HANDLING OF PRODUCT.
DEVELOPMENTAL EFFECTS: NONE IN ROUTINE HANDLING OF PRODUCT.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: NONE IN ROUTINE HANDLING OF PRODUCT.

PERSISTENCE/DEGRADABILITY: NONE IN ROUTINE HANDLING OF PRODUCT.

BIOACCUMULATION/ACCUMULATION: NONE IN ROUTINE HANDLING OF PRODUCT.

MOBILITY IN ENVIRONMENT: NONE IN ROUTINE HANDLING OF PRODUCT.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL:
DISPOSE IN ACCORDANCE WITH APPROPRIATE REGULATIONS. ALWAYS CONSULT AND OBEY
ALL INTERNATIONAL, FEDERAL, PROVINCIAL/STATE AND LOCAL HAZARDOUS WASTE
DISPOSAL LAWS. SOME JURISDICTIONS REQUIRE RECYCLING OF THIS SPENT PRODUCT.
BATTERY RECYCLING IS ENCOURAGED. LITHIUM ION BATTERIES ARE SAFE FOR DISPOSAL
IN THE NORMAL MUNICIPAL WASTE STREAM SINCE THEY ARE NOT DEFINED BY THE
FEDERAL GOVERNMENT AS HAZARDOUS WASTE. HOWEVER, LITHIUM ION BATTERIES ARE
RECYCLABLE.

THIS PRODUCT DOES NOT CONTAIN MERCURY, CADMIUM OR LITHIUM (METAL).

DO NOT INCINERATE OR SUBJECT BATTERY CELLS TO TEMPERATURES IN EXCESS OF 212
DEG. F (100 DEG. C).

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT HMR (RE: GROUND TRANSPORT):

PROPER SHIPPING DESCRIPTION:
UN3090 LITHIUM BATTERIES/UN3091 LITHIUM BATTERIES PACKED WITH OR CONTAINED
IN EQUIPMENT; CLASS 9; PG II.

MILWAUKEE RECHARGEABLE LITHIUM-ION TYPE BATTERIES ARE "EXCEPTED" FROM FULL
HAZARDOUS MATERIAL REGULATION BASED ON ELC CONTENT OR WH, AND COMPLIANT
PACKAGING PER 49 CFR 172.102, SPECIAL PROVISION 188.

CANADA TDG (RE: GROUND TRANSPORT):

PROPER SHIPPING DESCRIPTION:
UN3480 LITHIUM-ION BATTERIES/UN3481 LITHIUM-ION BATTERIES PACKED WITH OR
CONTAINED IN EQUIPMENT; CLASS 9; PG II.

MILWAUKEE RECHARGEABLE LITHIUM-ION BATTERIES ARE "EXCEPTED" FROM FULL
DANGEROUS GOODS REGULATION BASED ON WATT-HOURS (WH), AND COMPLIANT PACKAGING

PER TDG SCHEDULE 2, SPECIAL PROVISION 34.

INTERNATIONAL DGR (RE: AIR, SEA, GROUND TRANSPORT):

PROPER SHIPPING DESCRIPTION:
UN3480 LITHIUM-ION BATTERIES/UN3481 LITHIUM-ION BATTERIES PACKED WITH OR
CONTAINED IN EQUIPMENT; CLASS 9; PG II.

MILWAUKEE RECHARGEABLE LITHIUM-ION BATTERIES ARE "EXCEPTED" FROM FULL
DANGEROUS GOODS REGULATION BASED ON WATT-HOUR (WH) RATING AND COMPLIANT
PACKAGING AS DESCRIBED IN THE FOLLOWING INTERNATIONAL DANGEROUS GOOD
REGULATIONS:

ICAO TECHNICAL INSTRUCTIONS: PACKING INSTRUCTIONS 965; 966; 967.

IATA DANGEROUS GOODS REGULATIONS: PACKING INSTRUCTIONS 965; 966; 967.

IMDG CODE: SPECIAL PROVISION 188.

UN MODEL REGULATIONS ON THE TRANSPORT OF DANGEROUS GOODS:
SPECIAL PROVISION 188.

UN EUROPEAN AGREEMENTS (ADR/RID/ADN): SPECIAL PROVISION 188.

AUSTRALIAN DANGEROUS GOODS (ADG): SPECIAL PROVISION 188.

UN BATTERY TESTING:
MILWAUKEE RECHARGEABLE LITHIUM-ION BATTERIES LISTED IN SECTION 1 HAVE PASSED
THE RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN THE UN MANUAL
OF TESTS AND CRITERIA, PART III, SECTION 38.3, "LITHIUM BATTERIES".

UN SECTION 38.3 TEST REPORTS ARE MAINTAINED ON FILE AT THE CORPORATE
HEADQUARTERS OF MILWAUKEE ELECTRIC TOOL CORPORATION LOCATED AT 13135 W.
LISBON RD., BROOKFIELD, WI, USA 53005-2550.

SECTION 15: REGULATORY INFORMATION

GLOBAL INVENTORIES:

TSCA:

UNITED STATES:
SEE SEC. 14. COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS
DESCRIBED IN THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

DSL:

CANADA:
SEE SEC. 14. COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS
DESCRIBED IN THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

ECL:

KOREA:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

PICCS:

PHILIPPINES:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

ENCS:

JAPAN:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

AICS:

AUSTRALIA:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

IECS:

CHINA:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

EINECS:

EUROPEAN UNION:
COMPLIANT WITH, RELEVANT TRANSPORTATION TEST REQUIREMENTS AS DESCRIBED IN
THE UN MANUAL OF TESTS & CRITERIA, PART III, SUB-SECTION 38.3.

SARA 313 INFORMATION:

SARA TITLE III SECTION 313:
THIS PRODUCT DOES NOT CONTAIN REGULATED LEVELS OF ANY TOXIC CHEMICAL SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND
AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART 372.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986
(PROPOSITION 65):
THIS PRODUCT DOES NOT CONTAIN REGULATED LEVELS OF ANY TOXIC CHEMICAL SUBJECT
TO THE REPORTING REQUIREMENTS OF CALIFORNIA SAFE DRINKING WATER AND TOXIC
ENFORCEMENT ACT OF 1986 (PROPOSITION 65)

WHMIS:

CANADIAN WORKPLACE:
THIS PRODUCT DOES NOT CONTAIN REGULATED LEVELS OF ANY TOXIC CHEMICAL SUBJECT
TO THE REPORTING REQUIREMENTS

SECTION 16: OTHER INFORMATION

NFPA 704:

NATIONAL FIRE PROTECTION ASSOCIATION:
HEALTH N/A
FIRE N/A
REACTIVITY N/A

0 = MINIMAL HAZARD
1 = SLIGHT HAZARDOUS
2 = MODERATE HAZARD