

Wallace/KOR
MSDS: A6930

ITEM: 4E847 - Thermal Mastic 8 Oz
ORDER: 0036423461 LP NUMBER: U771162030

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - A6930

Associated Grainger Items
4E847

THERMAL MASTIC
(REVISED JULY 2004)

REC'D JUN 28 2008

MATERIAL SAFETY DATA SHEET

SECTION I - COMPANY IDENTIFICATION

PRODUCT: THERMAL MASTIC
CAT. NO.: PM8, PM21, PM25, PM50
DISTRIBUTED BY:
VIRGINIA KMP CORPORATION
4100 PLATINUM WAY
DALLAS, TEXAS 75237
TELEPHONE NUMBERS:
OFFICE: 1-(214) 330-7731
EMERGENCY ONLY: 1-(800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)	EXPOSURE LIMITS: OSHA PEL	8 HR. TWA	ACGIH TLV
PETROLEUM DISTILLATE (CAS# 64741-96-4)	NE	NE	NE
CALCIUM CARBONATE (CAS# 471-34-1)	15 MG/M3 (DUST)	NE	NE
KAOLIN (CAS# 1332-58-7)	15 MG/M3 (DUST)	NE	NE
1-PROPENE, 2-METHYL - HOMOPOLYMER (CAS# 9003-27-4)	NE	NE	NE

SECTION III - HAZARDS IDENTIFICATIONS

EMERGENCY OVERVIEW:
CAUTION!
CAUSES SKIN AND EYE IRRITATION. INHALATION OF VAPORS MAY BE NARCOTIC OR ANESTHETIC.
POTENTIAL HEALTH EFFECTS:
INHALATION: CAUSES IRRITATION.
EYE CONTACT: LIQUID OR VAPORS ARE IRRITATING.
SKIN CONTACT: CAN CAUSE IRRITATION TO SKIN.
INGESTION:
INGESTION OF LIQUID WILL CAUSE GASTROINTESTINAL DISTRESS, IRRITATION AND POSSIBLY NAUSEA.
CHRONIC EFFECTS: NOT KNOWN.
NOTE:
CARCINOGENICITY:
LISTED IN NTP?
NO
IARC?
NO
OSHA REGULATED?
NO

SECTION IV - FIRST AID MEASURES

INHALATION:
REMOVE VICTIM TO FRESH AIR AND, IF NEEDED, IMMEDIATELY BEGIN ARTIFICIAL RESPIRATION. GIVE OXYGEN IF BREATHING IS LABORED. GET EMERGENCY MEDICAL HELP. CONTACT A PHYSICIAN IMMEDIATELY.
EYE CONTACT:
FLUSH EYES WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP AND PERSIST.
SKIN CONTACT:
FLUSH WITH WATER OR SOAP AND WATER FOR 15 MINUTES OR UNTIL ALL TRACES HAVE BEEN REMOVED. SEEK MEDICAL ATTENTION IF SYMPTOMS DEVELOP AND PERSIST.
INGESTION:
DO NOT INDUCE VOMITING. RINSE MOUTH OUT WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

SECTION V - FIRE FIGHTING MEASURES

FLASHPOINT (TEST METHOD): ABOVE 100 F
FLAMMABLE LIMITS:
LOWER: ND
UPPER: ND
AUTOIGNITION TEMPERATURE: ND
GENERAL HAZARD:

FIRE FIGHTING INSTRUCTIONS:
APPROACH FIRE FROM UPWIND SIDE. AVOID BREATHING SMOKE, FUMES, MIST OR VAPORS ON THE DOWNWIND SIDE. FIREFIGHTERS WEAR PROTECTIVE CLOTHING AND SELF CONTAINED BREATHING APPARATUS.

EXTINGUISHING MEDIA: CARBON DIOXIDE, WATER FOG OR SPRAY.

HAZARDOUS COMBUSTION PRODUCTS: SMOKE, CARBON DIOXIDE, CARBON MONOXIDE.

SECTION VI - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES:
EMERGENCY RESPONSE COORDINATOR MUST HAVE MANDATED TRAINING. ELIMINATE ALL IGNITION SOURCES.
SMALL SPILLS:
PICK UP WITH ABSORBENT MATERIALS AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL OR REUSE.
LARGE SPILLS:
EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCK OR PUMP TO STORAGE/SALVAGE VESSELS.

LAND SPILL:
CLEAN UP LEAKS/SPILLS IMMEDIATELY TO PREVENT SOIL OR WATER CONTAMINATION.

WATER SPILL: NOTIFY PROPER AUTHORITIES.

SECTION VII - HANDLING AND STORAGE

HANDLING:
AVOID CONTACT WITH SKIN, EYES AND CLOTHING. AFTER HANDLING THIS PRODUCT, WASH HANDS BEFORE EATING, DRINKING OR SMOKING. IF CONTACT OCCURS, REMOVE CONTAMINATED CLOTHING. IF NEEDED, TAKE FIRST AID ACTION SHOWN IN SECTION IV. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

STORAGE: STORE IN A COOL, DRY PLACE.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: LOCAL AND MECHANICAL VENTILATION RECOMMENDED.
PERSONAL PROTECTION:
NOT REQUIRED UNDER NORMAL CONDITIONS. USE BOOTS, APRONS, DRENCH SHOWERS, EYE WASH AS NEEDED FOR PROTECTION AGAINST SPILLS AND/OR SPLASHES. SELF-CONTAINED BREATHING APPARATUS REQUIRED IF EXPOSURE TO DECOMPOSITION PRODUCT IS LIKELY.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: ND
VAPOR DENSITY (AIR=1): ND
SPECIFIC GRAVITY (H2O=1): >1
EVAPORATION RATE (BUAC=1): ND
SOLUBILITY IN WATER: INSOLUBLE
VOC (G/L): 200 - 400
pH: NA
FREEZING POINT: ND
BOILING POINT: ND
APPEARANCE & ODOR: GRAY PASTE, SOLVENT ODOR.

SECTION X - STABILITY AND REACTIVITY

STABILITY: STABLE.
CONDITIONS TO AVOID: NA
MATERIALS TO AVOID: OXIDIZERS.
HAZARDOUS DECOMPOSITION PRODUCTS:
SMOKE, CARBON DIOXIDE AND CARBON MONOXIDE.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION XI - TOXICOLOGICAL INFORMATION

KAOLIN
TDLO: 590 G/KG (ORAL - RAT)
CALCIUM CARBONATE
500 MG/24 MOD (SKIN - RABBIT)
750 G/24 SEV (EYE - RABBIT)
LD50:
6450 MG/KG (ORAL - RAT)

SECTION XII - ECOLOGICAL INFORMATION

NA

SECTION XIII - DISPOSAL CONSIDERATIONS

DISPOSE OF IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT REGULATED MATERIAL

HAZARD CLASS: NA

IDENTIFICATION NUMBER: NA

DOT EMERGENCY GUIDE #: NA

REPORTABLE QUANTITY (RQ): NA

INTERNATIONAL: NA

SECTION XV - REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCE CONTROL ACT):
COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY
ACT): NONE LISTED.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): NONE LISTED.

CALIFORNIA PROPOSITION 65: NOT LISTED.

SECTION XVI - OTHER INFORMATION

STATE RIGHT-TO-KNOW PROGRAMS: MA, PA

NFPA RATINGS:

HEALTH: 1
FLAMMABILITY: 0
REACTIVITY: 0

HMIS PROTECTIVE EQUIPMENT: X SEE YOUR SUPERVISOR

PREPARED BY: VIRGINIA-KMP CORPORATION

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, EXPRESSED OR IMPLIED,
EXCEPT THAT IT IS ACCURATE TO THE BEST KNOWLEDGE OF VIRGINIA KMP. THE DATA
ON THIS SHEET RELATED ONLY TO SPECIFIC MATERIAL DESIGNATED HEREIN. VIRGINIA
KMP ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON THESE DATA.