MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS AND RELATED MATERIALS (Approved by U.S. Department of Labor 'Essentially Similar' to form OSHA-20)

DATE OF PREPARATION MANUFACTURER'S NAME 18-Aug-86 THE SHERWIN-WILLIAMS COMPANY 101 prospect Avenue N.W. Cleveland, Ohio 44115 INFORMATION TELEPHONE NO EMERGENCY TELEPHONE (216) 566-2902 (216) 566-2917

Section I -- PRODUCT IDENTIFICATION

- Trade Mark

PRODUCT NUMBERS AND COLORS PRODUCT NAME Cream Hardener D2 A 135H D2 A 145H

Cream Hardener for

S-W* Lite-Weight Plastic Filler (D2 A 135)

S-W* Hair Plastic Filler (D2 A 138)

S-W* Glass Plastic Filler (D2 A 139)

8-W* Regular Plastic Filler (D2 A 145)

Peroxide Catalyst

94-36-0 Dibenzoyl Peroxide THEN I CANDAIL No ingredient in this product is an IARC, NTP or OSHA listed carcinogen Section II -- HAZARDOUS INGREDIENTS by MEIDER ADDINGTO 5 724~VIND Hg/H3

Section III -- PHYSICAL DATA

BOILING RANGE (F) * VOLATILE VOLUME 2 9.29

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT >199 F PMCC

LEL N.A.

FLAMMABILITY CLASSIFICATION

EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

SPECIAL FIRE FIGHTING PROCEDURES Not Applicable Not Applicable

Section V -- HEALTH BAZARD DATA

EFFECTS OF OVEREXPOSURE THRESHOLD LIMIT VALUE -- See Section

Irritant to skin, eyes, and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

> **EMERGENCY AND FIRST AID PROCEDURES** Cream Hardener

If INHALED: If on SKIN: If affected, remove from exposure. Restore breathing. Keep warm and qui Wash affected area thoroughly with soap and water. Flush eyes with large amounts of water for 15 minutes. Get medical

attention.

Section VI -- REACTIVITY DATA

STABILITY -- Stable

HAZARDOUS DECOMPOSITION PRODUCTS By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION -- Will Not Occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. WASTE DISPOSAL METHOD

accordance with Pederal, State, and Local regulations regarding pollution. Incinerate in approved facility. Do not incinerate closed container. Dispose of in

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid conta with skin and eyes. Wash hands after using.

Protect against dust which may be generated by sanding or abrading the dried film.

VENTILATION Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.9

1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear respiratory device approved by NIOSH/HSHA for protection against materials in Section II. PROTECTIVE GLOVES

Required for long or repeated contact.

EYE PROTECTION Wear safety spectacles with unperforated sideshields

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY -- 3B PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closed when not in use. Transfer only to approved containers with compl and appropriate labeling. Do not take internally. Keep out of the reach of children. OTHER PRECAUTIONS

titanium dioxide, calcium carbonate, etc. (see ACGIH TLV List, Preface and Appendix D), which may be present at hazardous levels only during sanding or abrading of the dried film This product must be mixed with other components before use. Before opening the packag READ AND FOLLOW VARNING LABELS ON ALL COMPONENTS. This coating contains materials classified as nulsance particulates, for example

of use are outside our control, we make no varranties, express or implied, and assume liability in connection with any use of this information. This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CPR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on product may substantially alter the composition and hazards of the product. Since condition the information available at this time. Addition of reducers or other additives to thi

				(
		·		
				(.
				·
				*
				•