MATERIAL SAFETY DATA SHEET

Manufactured by:

Anderson

67 SURFLEX[®]

Product Prelude

Chemical Company

325 SOUTH DAVIS AVENUE LITCHFIELD, MINNESOTA 55355

(320) 693-2477

Special See Bottom Hazard of Page NFPA Hazard Rating*

`Flammability

Reactivity

Health

Revised: 11/24/2008

24-HOUR EMERGENCY PHONE #: 1-800-424-9300 (CHEMTREC) Supersedes: 6/8/2006

· 医囊膜膜 医多种囊性坏疽 医多种 医甲基磺基甲基磺基酚

I. IDENTIFICATION

Chemical Name And Synonyms:

Not applicable

DOT Shipping Name

Sodium Hydroxide Solution

Chemical Family:

PG

Alkali

DOT Hazard Class & I.D. Number Corrosive Material UN1824

H

Hazard

Corrosive to eyes and skin

pH, 1% Soln.: 12.8

S INGREDIENTS CAS NO. Toxic

Component Sodium hydroxide

1310-73-2

2 gm/M3

2 gm/M3

NA

**Toxic chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR §372). NA: Not applicable NE: Not established

III. PHYSICAL DATA

Boiling Point: Above 220°F

Form: Liquid

Specific Gravity: 1.358

Solubility In Water: Complete

Appearance: Clear, blue liquid

Odor: None

IV. FIRE AND EXPLOSION HAZARD DATA

Flashpoint: Not Applicable

Extinguishing Media: Not applicable.

Special Fire

Fighting Procedures: Although this product is not combustible, if a fire occurs in the near vicinity, good firefighting practice dictates the use of self-contained

breathing apparatus and other protective gear. Cool fire-exposed containers with water. Move fire exposed containers if it can be done without risk.

Unusual Fire And

Explosion Hazards: If the stock solution container breaks, the solution should be handled with care as it is corrosive. Direct contact with water can cause a

violent exothermic reaction.

V. HEALTH HAZARD DATA

Carcinogenic: The raw materials used in this product are not considered to be a carcinogen by ACGIH and OSHA.

Effects Of Over-exposure: Corrosive. Causes irritation (possibly severe), burns to the eyes. May cause permanent eye damage. Causes irritation (possibly severe), burns to the skin. Causes irritation (possibly severe), burns, pulmonary edema to the respiratory tract. Causes irritation (possibly severe), burns, nausea, vomiting to the gastrointestinal tract. The severity of effects depend on concentration and how soon after exposure the area is washed.

Emergency And First

Aid Procedures: Eyes: Flush immediately with water for 15 minutes. Lift upper and lower eyelids for complete rinsing. Get immediate medical attention. Skin: Flush with water for 15 minutes. If imitation persists after rinsing, get medical attention. Remove contaminated clothing and wash

before reuse. Discard contaminated leather goods.

Ingestion: Rinse mouth with water. Give water to dilute. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to a semi-comatose, comatose, convulsing or unconscious person.

Page 2; Product Name: Prelude

THE TRANSPORT OF THE PROPERTY OF THE PROPERTY

Stability - Unstable:

Stable: X

Conditions To Avoid: Acid or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming

flammable hydrogen gas.

Incompatibility: Acids, halogenated compounds, prolonged contact with aluminum, brass, bronze, copper, lead, fin, zinc or other alkali sensitive

(Materials To Avoid) metals or alloys. Avoid contact with leather, wool, organic nitro compounds.

Hazardous

Decomposition Products: Toxic fumes of sodium oxide.

VII. SPILL OR LEAK PROCEDURES

Steps To Be Taken in Case Material is Released Or Spilled:

Small spills can be diluted with a large amount of water and flushed to drain.

Large spills, wear appropriate persoanl protection and completely contain spilled material. Recover as much material as possible into containers for disposal or reuse. Remaining material may be diluted with water and neutralized with dilute acid. Flush spill area with water followed by a liberal covering of sodium bicarbonate.

Waste Disposal Method: Dispose of in accordance with local, state, and federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not required for normal use. If mist level is high, wear NIOSH approved respirator.

Ventilation: Adequate to keep mist level below the TLV.

Protective Gloves: Natural rubber, neoprene or nitrile gloves should be worn.

Eye Protection: Chemical goggles.

Protective Clothing: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Contaminated clothing

should be removed, then discarded or laundered. Suggested materials are natural rubber, neoprene or nitrile.

IX. SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing:

Do not get in eyes, on skin, or clothing. Wash thoroughly after handling. Do not breathe vapors or mists. Use with adequate ventilation. Keep containers tightly closed and properly labeled. NEVER add water to product. ALWAYS add product, with constant stirring, slowly to surface of water to minimize heat generation and spattering.

Other Precautions: Safety shower and eyewash stations should be provided in the areas where this product is handled.

X, REVISED INFORMATION

MSDS Status: Updated supplier information

The opinions expressed herein are those of qualified experts within ANDERSON Chemical Company. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of the product are not within the control of ANDERSON Chemical Company, it is the user's obligation to determine the conditions of safe use of the product.