

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)**RIISERE 1020P**

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name 3B Products Co., Inc.	Emergency Telephone Number (412) 339-4070
Address (Number, Street, City, State, and ZIP Code) 321 Greensburg Rd.	Telephone Number for Information SAME
Lower Burrell, PA 15068	Date Prepared 2-25-87
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

RIGHT-TO-KNOW INFORMATION: Contains Carbonates -
CAS 471-34-1, Petrolatum-CAS 84743-01-7, Sulfonates -
CAS 81789-86-4 and Hydrotreated Distillate - CAS 8052-41-3.
Contains no asbestos.

Section III — Physical/Chemical Characteristics

Boiling Point 1BP 312F BP 500F	Specific Gravity (H ₂ O = 1) .971
Vapor Pressure (mm Hg) 10 mm @ 100F	Melting Point
Vapor Density (AIR = 1) 4-5	Evaporation Rate (Butyl Acetate = 1) N/A
Solubility in Water 0	

Appearance and Odor**Black resinous -- typical hydrocarbon odor****Section IV — Fire and Explosion Hazard Data**

Flash Point (Method Used) 105F COC	Flammable Limits	LEL 1.1	UEL 6.0
Extinguishing Media CO₂; Dry Chemical; Foam			

Special Fire Fighting Procedures**Water may be used to cool containers; foam may be used with caution.****Unusual Fire and Explosion Hazards****Vapors are heavier than air and may travel long distances to fire sources.**

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)

Strong oxidizing agents.

Hazardous Decomposition or Byproducts

None

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	X	X	

Health Hazards (Acute and Chronic)

Carcinogenicity:	NTP?	ARC Monographs?	OSHA Regulated?

Signs and Symptoms of Exposure

Acute--excessive inhalation can cause depression--usually reversible.

Medical Conditions

Generally Aggravated by Exposure

Emergency and First Aid Procedures

Flush eyes with water for 15 min; remove contaminated clothing; wash skin with soap and water; remove exposed person to fresh air.**Section VII — Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled

Remove all sources of fire; put in closed containers; absorb spills with dry sand or absorbent material. Clean area with detergent and water solutions. Do not flush into sewer.

Waste Disposal Method

Dispose in approved land fill.

Precautions to Be Taken in Handling and Storing

Store in cool area away from fire sources in approved containers.

Other Precautions

Section VIII — Control Measures

Respiratory Protection (Specify Type)

Use NIOSH approved carbon filter mask

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves

Use protective synthetic rubber gloves

Eye Protection

Plastic goggles

Other Protective Clothing or Equipment

Normal work clothes

Work/Hygiene Practices