

THE ASSEMBLY PROFESSIONALS

WURTH USA Midwest Inc.

385 Kimberly Drive Carol Stream, IL 60188 (800) WURTH USA

WURTH USA Northeast Inc. 93 Grant Street

Ramsey, NJ 07446 (800) WURTH USA WURTH USA Southeast Inc. 8501 Parkline Blv.

Orlando, FL 32809 (800) WURTH USA WURTH USA West Inc. 1486 Cedar Street Ontario, CA 91761

(800) WURTH USA

24-Hour WURTH MSDS Fax Hotline (201) 828-5871 or 1-888-WURTH Fax

MATERIAL SAFETY DATA SHEET

DIVISION:

Automotive

TRADE NAME: Grev seam sealer PRODUCT NUMBER: 8901013 DATE PREPARED: May 14, 1998

1. HAZARDOUS INGREDIENTS	CAS#	PERCENT	OSHA PEL	ACGIH TLV
Xylene	1330-20-7	30-60	N/A	N/A
Oil, mineral	54745-52-5	10-30	N/A	N/A
Nonhazardous pigments	N/A`	10-30	N/A	N/A
Nonhazardous resin	N/A	10-30	N/A	N/A
Fumed Silica	7631-86-9	3-7	N/A	N/A

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 & 40 CFR **PART 372.**

2. PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT:

N/A

VAPOR DENSITY (AIR=1):

VAPOR PRESSURE (mm HG): N/A

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: Slight

SPECIFIC GRAVITY: 0.98

VOLATILE ORGANICS: N/A PERCENT VOLATILE: 43.21

PH: N/A

MELTING POINT: N/A VISCOSITY: N/A

APPEARANCE AND ODOR:

Gray to black pungent

liquid

3. FIRE AND EXPLOSION HAZARD

FLASHPOINT AND TEST METHOD USED:

FLAMMABLE LIMITS:

75°F, 24°C LEL:

.N/A

UEL:

N/A

EXTINGUISHING METHOD: SPECIAL FIRE FIGHTING PROCEDURES:

Waterfog, CO2, dry chemical, foam

N/A **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

NFPA HAZARD CLASS:

HEALTH:

N/A

FIRE: N/A REACTIVITY: N/A

4. REACTIVITY DATA

STABILITY: Avoid excessive heating over long periods of time

HAZARDOUS POLYMERIZATION: CONDITIONS TO AVOID:

Will not occur

MATERIALS TO AVOID: N/A

Heat, open flames, spark

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

5. ENVIRONMENTAL DATA

RECOMMENDED DISPOSAL:

SPILL RESPONSE: Remove all sources of ignition. Remove to a container or absorb with clay, diatomaceous earth or

other suitable inert absorbent

Dispose of by controlled burning or landfill the absorption material in an approved site in accordance with local, provincial, and federal regulations.

PRECAUTIONS TO BE TAKEN WHEN HANDLING OR STORING:

Provide adequate ventilation. Avoid prolonged breathing of vapors. Do not incinerate closed containers



THE ASSEMBLY PROFESSIONALS

WURTH USA Midwest Inc.

385 Kimberly Drive Carol Stream, IL 60188 (800) WURTH USA

WURTH USA Northeast Inc. 93 Grant Street Ramsey, NJ 07446

(800) WURTH USA

WURTH USA Southeast Inc. 8501 Parkline Blv. Orlando, FL 32809 (800) WURTH USA **WURTH USA** West Inc. 1486 Cedar Street Ontario, CA 91761 (800) WURTH USA

24-Hour WURTH MSDS Fax Hotline (201) 828-5871 or 1-888-WURTH Fax

MATERIAL SAFETY DATA SHEET -- PAGE 2

PRODUCT NUMBER: 8901013

6. CONTROL MEASURES

RESPIRATORY PROTECTION: When respiratory protection is required, use an approved air purifying respirator Provide general dilution or local exhaust in volume and pattern to keep TLV of hazardous ingredients VENTILATION:

below acceptable limits

PROTECTIVE GLOVES: Use impervious gloves

EYE PROTECTION: Use chemical goggles and full face shield.

OTHER PROTECTIVE MEASURES: Wear clean, long sleeved, body covering clothing, Avoid inhalation, skin and eye

contact.

7. HEALTH HAZARD DATA

ROUTE OF ENTRY:

INHALATION: Х

SKIN: Х EYES: Х

INGESTION: Х

HEALTH HAZARDS(acute & chronic): Overexposure may result in damage to kidney and liver

SIGNS AND SYMPTOMS OF EXPOSURE:

INHALATION:

High vapor concentration may produce nausea, vomiting, headaches, dizziness, unconsciousness and

asphyxia resulting in central nervous system effects

SKIN: will result in skin irritation. **EYES:** will result in eye irritation.

INGESTION:

may lead to gastrointestinal irritation or ulceration.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: remove to fresh air. If breathing is difficult, administer oxygen.

SKIN CONTACT: Wash the exposed area with soap and water immediately. Call a physician if irritation persists.

EYE CONTACT: Flush thoroughly with water for at least 15 minutes and get immediate medical attention.

DO NOT INDUCE VOMITING. Transport to a medical facility. IF SWALLOWED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED DUE TO EXPOSURE:

CARCINOGENIC:

NPT?***

IARC MONOGRAPHS***

OSHA REGULATED***

*** NOT PRESENTLY ON ANY LIST

ABBREVIATIONS -

N/D - Not Determined

N/A - Not Applicable

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THE TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OF THEIR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED. AND ASSUME NO LIABILITY IN CONNECTION WITH ANY OF THIS INFORMATION.