

MATERIAL SAFETY
DATA SHEET

3M
3M Center
St. Paul, Minnesota
55144-1000
1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2000, Minnesota Mining and Manufacturing Company.
All rights reserved. Copying and/or downloading of this
information for the purpose of properly utilizing 3M products
is allowed provided that:

- 1) the information is copied in full with no changes unless
prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
distributed with the intention of earning a profit thereon.

DIVISION: AUTOMOTIVE AFTERMARKET

TRADE NAME:

3M(TM) Perfect-It(TM) II Rubbing Compound - Paste, P.N. 05983

ID NUMBER/U.P.C.:

60-9800-2212-7 00-51131-05983-2

ISSUED: October 18, 2000

SUPERSEDES: September 29, 2000

DOCUMENT: 07-1516-9

1. INGREDIENT	C.A.S. NO.	PERCENT
WATER.....	7732-18-5	30.0 - 60.0
QUARTZ SILICA (CRYSTALLINE SILICA).....	14808-60-7	10.0 - 30.0
HYDROTREATED LIGHT PETROLEUM DISTILLATES.....	64742-47-8	10.0 - 30.0
KAOLINITE.....	1318-74-7	7.0 - 13.0
GLYCERIN.....	56-81-5	1.0 - 5.0
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES.....	64741-88-4	1.0 - 5.0
OLEIC ACID.....	112-80-1	1.0 - 5.0
POLY(OXYETHYLENE)SORBITAN MONOSTEARATE..	9005-67-8	1.0 - 5.0
MINERAL OIL.....	64741-89-5	< 2.0

The components of this product are in compliance with the chemical
notification requirements of TSCA. All applicable chemical
ingredients in this material are listed on the European Inventory of
Existing Chemical Substances (EINECS), or are exempt polymers whose
monomers are listed on EINECS.

2. PHYSICAL DATA

BOILING POINT:..... 150 - 212 F
VAPOR PRESSURE:..... < 1 Air=1
VAPOR DENSITY:..... > 1.00 Air=1
EVAPORATION RATE:..... 1.00 Water=1
SOLUBILITY IN WATER:..... complete
SPECIFIC GRAVITY:..... 1.0 - 1.2 Water=1
PERCENT VOLATILE:..... 60 - 65 %

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA (continued)

pH:..... 7.8 - 8.5
VISCOSITY:..... 80000 - 120000 centipoise
MELTING POINT:..... N/D

APPEARANCE AND ODOR:

Liquid, Mild Solvent Odor, Cream Color

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... 155 F PMCC
Firepoint: 150 F.
FLAMMABLE LIMITS - LEL:..... N/D
FLAMMABLE LIMITS - UEL:..... N/D
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Water, Dry chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Water may be used to blanket the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

No unusual fire or explosion hazards are anticipated.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 1 REACTIVITY: 0

UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Not applicable

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Strong Oxidizing Agents.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Observe precautions from other sections. Ventilate area. Contain spill. Cover with absorbent material. Collect spilled material. Clean up residue with water. Place in a closed container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility in the presence of a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 2.03 lb/gal calculated per SCAQMD rule 443.1.
Volatile Organic Compounds: 244 gms/liter calculated per SCAQMD rule 443.1.
VOC Less H2O & Exempt Solvents: 377 gms/liter calculated per SCAQMD rule 443.1.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: nitrile rubber.

RECOMMENDED VENTILATION:

Use in a well-ventilated area. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors. Avoid prolonged breathing of dust. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask dust and mist respirator, Half-mask organic vapor respirator with dust/mist prefilter, full-face dust and mist respirator, full-face organic vapor respirator with dust/mist prefilter

The use of a proper government approved respirator is required if contaminant concentrations exceed the OSHA Permissible Exposure Limit (PEL) or Threshold Limit Value (TLV).

PREVENTION OF ACCIDENTAL INGESTION:

Wash hands after handling and before eating. Do not ingest.

RECOMMENDED STORAGE:

Store in a cool place. Store out of direct sunlight. Keep container closed when not in use. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
WATER.....	NONE	NONE	NONE	NONE	
QUARTZ SILICA (CRYSTALLINE SILICA)...	0.1	MG/M3	TWA	OSHA	
		as quartz resp. dust			
QUARTZ SILICA (CRYSTALLINE SILICA)...	0.05	MG/M3	TWA	ACGIH	
		as quartz resp. dust			
HYDROTREATED LIGHT PETROLEUM					
DISTILLATES.....	300	PPM	TWA	CMRG	
KAOLINITE.....	NONE	NONE	NONE	NONE	
GLYCERIN.....	10	MG/M3	TWA	ACGIH	

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
GLYCERIN.....	10	MG/M3	TWA	OSHAV	
	AS MIST				
GLYCERIN.....	15	MG/M3	TWA	OSHA	
	AS MIST				
	OSHA VACATED PEL: TOTAL DUST				
GLYCERIN.....	5	MG/M3	TWA	OSHA	
	TOTAL DUST				
	AS MIST				
	RESPIRABLE FRACTION				
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES.....	5	MG/M3	TWA	CMRG	
OLEIC ACID.....	NONE	NONE	NONE	NONE	
POLY(OXYETHYLENE) SORBITAN MONOSTEARATE.....	NONE	NONE	NONE	NONE	
MINERAL OIL.....	5	MG/M3	TWA	ACGIH	
	as mist				
MINERAL OIL.....	10	MG/M3	STEL	ACGIH	
	as mist				
MINERAL OIL.....	5	MG/M3	TWA	OSHA	
	as mist				

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL.
Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Mild Eye Irritation: signs/symptoms can include redness, swelling, pain, and tearing.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

INHALATION:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

During buffing pad spurring:

Silicosis: signs/symptoms can include shortness of breath and persistent coughing.

WARNING: Airborne crystalline silica generated from the dry buff pads may produce dust conditions in excess of the OSHA Permissible Exposure Limit (PEL) or Threshold Limit Value (TLV) for crystalline silica. The use of a proper government approved respirator is required if contaminant concentrations exceed the PEL or TLV.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

CANCER:

WARNING: Contains a chemical which can cause cancer. (14808-60-7)
(NTP known human carcinogen, IARC human carcinogen 1, Calif. Proposition 65)

SECTION CHANGE DATES

PRECAUTIONARY INFO. SECTION CHANGED SINCE September 29, 2000 ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

